

Mode			
Item		MILL25FS	MILL35FS
Cooling capacity(Btu/h)		9000	12000
Heating capacity(Btu/h)		9500	13000
Power supply(V/Ph/Hz)		220-230/1/50	220-230/1/50
Cooling	Rated Input (W)	850	1180
	Rated Current (A)	3.6	5.7
	EER(Btu/h/W)	10.6	10.2
Heating	Rated Input (W)	840	1200
	Rated Current (A)	3.8	9.2
	COP(Btu/h/W)	10.8	10.8
Indoor Unit	Airflow Rate(m ³ /h)	450	570
	Noise Level dB(A)	≤40	≤42
	Outline Dimensions(mm) (WXHxD)	790*265*175	865*285*190
	Packing Dimensions(cm) (WXHxD)	865*245*310	940*355*245
	Weight(Net/Gross) (Kg)	8/11	10/13
	Dehumidity(Kg/h)	1.0	1.4
Outdoor Unit	Compressor Type	Rotary	Rotary
	Starting Current(A)	28.0	38.5
	Defrost Method	Reversing cycle	Reversing cycle
	Noise Level dB(A)	52	52
	Outline Dimensions(mm) (WXHxD)	870*560*270	870*560*270
	Packing Dimensions(cm) (WXHxD)	920*600*355	920*600*360
	Weight(Net/Gross) (Kg)	29/32	33/36
Refrigerant		R410A	R410A
Connection Tube	Liquid Tube(Inch mm)	1/4" φ6.35	1/4" φ6.35
	Gas Tube(Inch mm)	3/8" φ9.52	1/2" φ12.7
	Max.length(m)	4	4
	Max.height(m)	4	4
	Connecting Type	Quick Couple	Quick Couple