

Mode		MILL25DC	MILL35DC
Item			
Cooling capacity(Btu/h)		4500-12000	6000-14000
Heating capacity(Btu/h)		5000-13000	7000-16000
Power supply(V/Ph/Hz)		220-240/1/50	220-240/1/50
Cooling	Rated Input (W)	320-1300	770-1450
	Rated Current (A)	1.6-6.2	2.3-7.7
	EER(W/W)	3.25	3.22
Heating	Rated Input (W)	300-1350	600-1450
	Rated Current (A)	1.5-6.5	2.1-8.6
	COP(W/W)	3.41	3.5
Indoor Unit	Airflow Rate(m ³ /h)	420	520
	Noise Level dB(A)	36	38
	Outline Dimensions(mm) (WXHxD)	785*260*190	785*260*190
	Packing Dimensions(cm) (WXHxD)	87X33X28	87X33X28
	Weight(Net/Gross) (Kg)	9/12	9/12
	Dehumidity(Kg/h)	1.0	1.15
Outdoor unit	Noise Level dB(A)	51	51
	Outline Dimensions(mm) (WXHxD)	870*560*320	870*560*320
	Packing Dimensions(cm) (WXHxD)	93X60X37	93X60X37
	Weight(Net/Gross) (Kg)	32/35	32/35
Refrigerant Type		R410a	R410a
Refrigerant Charge(gr.)		750	850
Connection Tube	Liquid Tube(Inch mm)	1/4" φ6.35	1/4" φ6.35
	Gas Tube(Inch mm)	3/8" φ9.52	3/8" φ9.52
	Max.length(m)	5	5
	Max.height(m)	5	5
	Connecting Type	Quick Couple	Quick Couple